



Product Features and Specifications

- Standard refrigerant connections: liquid line - 3/8" ODS, suction line - 7/8" ODS.
- Two 3/4" MPT condensate drains.
- Powder-painted metal drain pan. Stainless available.
- Bi-directional airflow.
- Flowrate standard. Factory or field-installable TXV available.
- Immersion-tested at 500 psi, then nitrogen-pressurized and sealed.
- Heavy gauge embossed galvanized cabinet fully lined with 1/2" faced insulation.
- Rifled copper tubing, enhanced aluminum fins.
- AHRI certifiable with all brands of A/C and heat pump systems (BHA only).
- ETL listed for use with R-410A, R-454B, and R-32 when proper metering device is used.
- Five-year warranty. For complete warranty details, please visit www.AspenMfg.com



Representative drawing only. Some models may vary in appearance.

COIL MODEL	DIMENSIONS				
	HEIGHT (H)"	WIDTH (W)"	DEPTH (D)"	OPENINGS	
				(C)"	(B)"
HIGH HORIZONTAL					
BHA** 24	23-1/2	21-1/2	10	21	16
BHA** 36		29-1/2			24
BHA** 48		34-1/2			29
BHA** 60	25				
LOW HORIZONTAL					
BHL** 24	17	27	10	14-1/2	21-1/2
BHL** 36		36			29
BHL** 48	21			18-1/2	
BHL** 60					

DRAIN PAN TEMPERATURE TABLE	
DRAIN PAN TYPE	TEMP LIMITS
Plastic - Standard	290°
Plastic - High Temp	425°
Metal - High Temp	600°

ASK FOR ASPEN

BHAL Spec-2024-12

In keeping with its commitment to continuous improvement, Aspen Manufacturing reserves the right to make changes without notice and incurring obligation.