



Unit shown with service panels removed. Representative image only. Some models may vary in appearance. Duct opening dimensions can be ascertained by subtracting 1-1/2" for top opening width/depth, 3/4 for bottom opening. Due to continuous product improvement, specifications are subject to change without notice.

For complete warranty details visit www.AspenMfg.com

Product Features and Specifications

- Rifled copper tubing, enhanced aluminum fins.
- Immersion-tested at 500 psi, then nitrogen-pressurized and sealed.
- Left or right-hand refrigerant and plumbing connections.
- Liquid line - 3/8" ODS, suction line - 3/4 ODS on 1-1/2 3 ton and 7/8 ODS on 3-1/2 - 5 ton.
- Externally mounted flowrater body with Schrader valve for hiss-testing
- Heavy duty plastic drain pans on most models.
- Embossed galvanized cabinets standard. Cabinets feature furnace connectors (patent pending).
- Upflow without field modification. Downflow applications require plate kit, sold separately.
- Split access doors in front for easy access.
- Fully insulated cabinets with faced insulation.
- Ten-year limited warranty.
- AHRI certifiable with all brands of A/C and heat pump systems.
- ETL listed for use with R-22, R-410A, R-454A, and R-32 when proper metering device is used.

Customization

- Factory or field-installed TXV available
- Painted cabinets
- Powder-painted metal or stainless pans
- Schrader mounted on suction manifold, external to cabinet
- Bikini cabinets

Downflow Kit Part Numbers

- **METAL DRAIN PANS** 16" DWNFLWM-16 & 18" DWNFLWM-18
- **PLASTIC DRIAN PANS** DWNFLWP

COIL MODEL	NOMINAL CAPACITY (BTUs)	PISTON SIZE R 410-A	DIMENSIONS				SHIPPING INFORMATION			
			CABINET WIDTH		CABINET DEPTH	CABINET HEIGHT	SHIPPING WEIGHT (LBS)			SKID QTY
			MIN WIDTH	MAX WIDTH			2 ROW	3 ROW	4 ROW	
CC24A*	24,000	0.055	14	23	21-1/2	16	29	37	45	20
CC24B*		0.055	14	23	21-1/2	16	34	44	52	20
CC24C*		0.055	14	23	21-1/2	20	39	50	59	16
CC24D*		0.055	14	23	21-1/2	20	44	56	67	16
CC30A*	30,000	0.059	14	23	21-1/2	16	34	44	52	20
CC30B*		0.059	14	23	21-1/2	20	39	50	59	16
CC30C*		0.059	14	23	21-1/2	20	44	56	67	16
CC30D*		0.059	14	23	21-1/2	24	49	62	74	12
CC30E*		0.059	14	23	21-1/2	24	51	64	76	12
CC36A*	36,000	0.068	2/3R - 14, 4R-17	23	21-1/2	20	39	50	59	16
CC36B*		0.068	2/3R - 14, 4R-17	23	21-1/2	20	44	56	67	16
CC36C*		0.068	2/3R - 14, 4R-17	23	21-1/2	24	49	62	74	12
CC36D*		0.068	2/3R - 14, 4R-17	23	21-1/2	24	54	69	82	12
CC36E*		0.068	2/3R - 14, 4R-17	23	21-1/2	20	39	50	59	16
CC36F*		0.068	17	26-1/2	21-1/2	28	63	81	96	12
CC42A*	42,000	0.074	17	26-1/2	21-1/2	20	44	56	67	16
CC42B*		0.074	17	26-1/2	21-1/2	24	49	62	74	12
CC42C*		0.074	17	26-1/2	21-1/2	24	54	69	82	12
CC42D*		0.074	17	26-1/2	21-1/2	28	59	75	89	12
CC42E*		0.074	17	26-1/2	21-1/2	20	44	45	67	16
CC42F*		0.074	17	26-1/2	21-1/2	28	63	81	96	12

COIL MODEL	NOMINAL CAPACITY (BTUs)	PISTON SIZE R 410-A	DIMENSIONS				SHIPPING INFORMATION			
			CABINET WIDTH		CABINET DEPTH	CABINET HEIGHT	SHIPPING WEIGHT (LBS)			SKID QTY
			MIN WIDTH	MAX WIDTH			2 ROW	3 ROW	4 ROW	
CC48A*	48,000	0.080	17	26-1/2	21-1/2	24	49	62	74	12
CC48B*		0.080	17	26-1/2	21-1/2	24	54	69	82	12
CC48C*		0.080	17	26-1/2	21-1/2	28	58	75	89	12
CC48D*		0.080	17	26-1/2	21-1/2	28	63	81	96	12
CC48F*		0.080	17	26-1/2	21-1/2	28	60	77	91	12
CC48G*		0.080	17	26-1/2	21-1/2	28	65	83	98	12
CC60A*	60,000	0.089	20-1/2	26-1/2	21-1/2	28	58	75	89	12
CC60B*		0.089	20-1/2	26-1/2	21-1/2	28	63	81	96	12
CC60C* (3)		0.089	20-1/2	26-1/2	23	28	66	84	100	12
CC60D* (3)		0.089	20-1/2	26-1/2	23	28	71	91	108	12
CC60E* (3)		0.089	20-1/2	26-1/2	21-1/2	28	79	101	120	12
CC60F*		0.089	20-1/2	26-1/2	21-1/2	28	60	77	91	12
CC60G* (4)		0.089	20-1/2	26-1/2	21-1/2	28	81	103	122	12

DRAIN PAN TEMPERATURE TABLE	
DRAIN PAN TYPE	TEMP LIMITS
Plastic - Standard	290°
Plastic - High Temp	425°
Metal - High Temp	600°