



Product Features and Specifications

- Rified copper tubing, enhanced aluminum fins.
- Immersion-tested at 500 psi, then nitrogen-pressurized and sealed.
- Left or right-hand refrigerant and plumbing connections.
- Liquid line - 3/8" ODS, suction line - 3/4" ODS on 1-1/2 3 ton and 7/8" ODS on 3-1/2 - 5 ton.
- Externally mounted flowrater body with Schrader valve for hiss-testing
- Heavy duty plastic drain pans on most models.
- Upflow without field modification. Downflow applications require plate kit, sold separately.
- AHRI certifiable with all brands of A/C and heat pump systems.
- ETL listed for use with R-22, R-410A, R-454B, and R-32 when proper metering device is used.
- Ten-year limited warranty. For complete warranty details, please visit www.AspenMfg.com

Customization

- Factory or field-installed TXV available.
- Powder-painted metal or stainless pans.
- Schrader mounted on suction manifold, external to cabinet.

Downflow Kit Part Numbers

- | | |
|-------------------------|---------------------------|
| METAL DRAIN PANS | PLASTIC DRAIN PANS |
| • 16" DWNFLWM-16 | • DWNFLWP |
| • 18" DWNFLWM-18 | |

Representative image only. Some models may vary in appearance. Due to continuous product improvement, specifications are subject to change without notice.

COIL MODEL	NOMINAL CAPACITY (BTUs)	PAN DIMENSIONS					SHIPPING INFORMATION						
		WIDTHS (W)"				DEPTH (D)"	BARE SLAB HEIGHT (H)"	SHIPPING WEIGHT (LBS)			SKID QTY		
		13	16	19-1/2	23			2 ROW	3 ROW	4 ROW			
CA24A*	24,000	13	16	19-1/2	23	19-3/8	13-1/2	17	27	35	30		
CA24B*							15-1/2	20	31	41		25	
CA24C*							17-1/2	23	36	47			
CA24D*							19-1/2	25	40	53			
CA30A*	30,000	13	16	19-1/2	23	19-3/8	15-1/2	20	31	41	25		
CA30B*							17-1/2	23	36	47			
CA30C*							19-1/2	25	40	53	20		
CA30D*							21-1/2	28	45	58			
CA30E*							30	47	60	16			
CA36A*	36,000	13 for 2, 3R; 16 for 4R	16	19-1/2	23	19-3/8	17-1/2	23	36	47	25		
CA36B*							19-1/2	25	40	53	20		
CA36C*							21-1/2	28	45	58	16		
CA36D*							23-1/2	31	49	64	12		
CA42A*	42,000	N/A	16	19-1/2	23	19-3/8	25-1/2	25	40	53	20		
CA42B*							21-1/2	28	45	58	16		
CA42C*							23-1/2	31	49	64	12		
CA42D*							25-1/2	34	54	70			
CA48A*	48,000	N/A	16	19-1/2	23	19-3/8	21-1/2	28	45	58	16		
CA48B*							23-1/2	31	49	64	12		
CA48C*							25-1/2	34	54	70			
CA48D*							27-1/2	37	58	76			
CA48F*							25-1/2	36	56	72			
CA48G*							27-1/2	39	60	78			
CA60A*	60,000	N/A	16	19-1/2 (2)	23 (2)	21-3/4	25-1/2	34	54	70		12	
CA60B*							27-1/2	37	58	76			
CA60C*							24-1/2	38	60	79			
CA60D*							26-1/2	41	65	86			
CA60E*							N/A	24 (3)	21	46	73		95
CA60F*							19-1/2	23	19-3/8	25-1/2	41		62
CA60G*	N/A	24 (3)	21	26-1/2	48	75	97						

CA Spec-2024-12

In keeping with its commitment to continuous improvement, Aspen Manufacturing reserves the right to make changes without notice and incurring obligation.

DRAIN PAN TEMPERATURE TABLE

DRAIN PAN TYPE	TEMP LIMITS
Plastic - Standard	290°
Plastic - High Temp	425°
Metal - High Temp	600°