



Unit shown with service panels removed. Representative image only. Some models may vary in appearance. Duct opening dimensions can be ascertained by subtracting 1-1/2" for top opening width/depth, 3/4 for bottom opening. Due to continuous product improvement, specifications are subject to change without notice.

### Product Features and Specifications

- Rifled copper tubing, enhanced aluminum fins.
- Immersion-tested at 500 psi, then nitrogen-pressurized and sealed.
- Left or right-hand refrigerant and plumbing connections.
- Liquid line - 3/8" ODS, suction line - 3/4 ODS on 1-1/2 3 ton and 7/8 ODS on 3-1/2 - 5 ton.
- Externally mounted flowrater body with Schrader valve for hiss-testing.
- Heavy duty plastic drain pans on most models.
- Embossed galvanized cabinets standard. Cabinets feature furnace connectors (patent pending).
- Upflow without field modification. Downflow applications require plate kit, sold separately.
- Split access doors in front for easy access.
- Fully insulated cabinets with faced insulation.
- AHRI certifiable with all brands of A/C and heat pump systems.
- ETL listed for use with R-22, R-410A, R-454B, and R-32 when proper metering device is used.
- Ten-year limited warranty. For complete warranty details, please visit [www.AspenMfg.com](http://www.AspenMfg.com)

### Customization

- Factory or field-installed TXV available.
- Painted cabinets.
- Powder-painted metal or stainless pans.
- Schrader mounted on suction manifold, external to cabinet.
- Bikini cabinets.

### Downflow Kit Part Numbers

- **METAL DRAIN PANS**
  - 16" DWNFLWM-16
  - 18" DWNFLWM-18
- **PLASTIC DRAIN PANS**
  - DWNFLWP

COIL MODEL	NOMINAL CAPACITY (BTUs)	CABINET DIMENSIONS				SHIPPING INFORMATION			
		MIN. WIDTH	MAX. WIDTH (W)"	DEPTH (D)"	HEIGHT (H)"	WEIGHT (LBS)			SKID QTY
						2 ROW	3 ROW	4 ROW	
CC24A*	24,000	14	23	21-1/2	16	29	37	45	20
CC24B*						34	44	52	
CC24C*					20	39	50	59	16
CC24D*						44	56	67	
CC30A*	30,000	14	23	21-1/2	16	34	44	52	20
CC30B*						39	50	59	
CC30C*					20	44	56	67	16
CC30D*						49	62	74	
CC30E*	36,000	2/3R - 14; 4R-17	23	21-1/2	24	51	64	76	12
CC36A*						39	50	59	
CC36B*					20	44	56	67	16
CC36C*						49	62	74	
CC36D*	42,000	17	26-1/2	21-1/2	24	54	69	82	12
CC36E*						39	50	59	
CC36F*					20	63	81	96	12
CC42A*						44	56	67	
CC42B*	48,000	17	26-1/2	21-1/2	24	49	62	74	12
CC42C*						54	69	82	
CC42D*					28	59	75	89	16
CC42E*						44	45	67	
CC42F*	48,000	17	26-1/2	21-1/2	28	63	81	96	12
CC48A*						49	62	74	
CC48B*					24	54	69	82	12
CC48C*						58	75	89	
CC48D*	28	63	81	96	12				
CC48F*		60	77	91					
CC48G*	48,000	17	26-1/2	21-1/2	28	65	83	98	12

COIL MODEL	NOMINAL CAPACITY (BTUs)	CABINET DIMENSIONS				SHIPPING INFORMATION			SKID QTY
		MIN. WIDTH	MAX. WIDTH (W)"	DEPTH (D)"	HEIGHT (H)"	WEIGHT (LBS)			
						2 ROW	3 ROW	4 ROW	
CC60A*	60,000	20-1/2	26-1/2	21-1/2	28	58	75	89	12
CC60B*				63		81	96		
CC60C* (3)				23		66	84	100	
CC60D* (3)						71	91	108	
CC60E* (3)				21-1/2		79	101	120	
CC60F*						60	77	91	
CC60G* (4)				81		103	122		

DRAIN PAN TEMPERATURE TABLE	
DRAIN PAN TYPE	TEMP LIMITS
Plastic - Standard	290°
Plastic - High Temp	425°
Metal - High Temp	600°

### ASK FOR ASPEN

CC Spec-2024-12

In keeping with its commitment to continuous improvement, Aspen Manufacturing reserves the right to make changes without notice and incurring obligation.