



Product Features and Specifications

- Rifled copper tubing, enhanced aluminum fins.
- Immersion-tested at 500 psi, then nitrogen-pressurized and sealed.
- Liquid line - 3/4" ODS, suction line - 3/4" ODS on 1-1/2-3 ton and 7/8" ODS on 3-1/2 - 5 ton.
- Externally mounted flowrater body with Schrader valve for hiss-testing.
- Split access doors for easy service.
- Fully insulated cabinets with faced insulation.
- AHRI certifiable with all brands of A/C and heat pump systems.
- ETL listed for use with R-22, R-410A, R-454B, and R-32 when proper metering device is used.
- Ten-year limited warranty. For complete warranty details, please visit www.AspenMfg.com

Customization

- Factory or field-installed TXV available.
- Schrader mounted on suction manifold, external to cabinet.

Unit shown with service panels removed. Representative drawing only. Some models may vary in appearance. Duct opening dimensions can be ascertained by subtracting 1-1/2" for top opening width/depth, 3/4" for bottom opening.

COIL MODEL	NOMINAL CAPACITY (BTUs)	DIMENSIONS					SHIPPING INFORMATION			
		CABINET		OPENING		LENGTH (E)"	WEIGHT (LBS)			SKID QTY
		WIDTH (A)"	HEIGHT (B)"	(C)"	(D)"		2 ROW	3 ROW	4 ROW	
CH24A*	24,000	10	23-1/2	21	16	21-1/2	20	34	N/A	14
CH24B*					24	29-1/2	29	43		
CH36A*	36,000				30	35-1/2	35	49		
CH36B*					36	41-1/2	42	56		
CH48A*	48,000				42	47-1/2	N/A	70	8	
CH48B*					42	47-1/2	N/A	80		
CH60A*	60,000									
CH60B*										

DRAIN PAN TEMPERATURE TABLE	
DRAIN PAN TYPE	TEMP LIMITS
Plastic - Standard	290°
Plastic - High Temp	425°
Metal - High Temp	600°

ASK FOR ASPEN

CH Spec-2025-01

In keeping with its commitment to continuous improvement, Aspen Manufacturing reserves the right to make changes without notice and incurring obligation.